

B5020 / B5020D / B5032 / B5032D
BQ5040

Slotting Machine 插床



B5020D/B5032D
带快移rapid traverse

B5050 / B5063
B50100 / B51125

Slotting Machine 插床



主要技术参数	SPECIFICATIONS	Units	B5020	B5020D	B5032	B5032D	BQ5040
滑枕最大插削长度	Max. ram slotting length	mm	200	200	320	320	400(内孔360)
滑枕运动次数	Ram moving frequency per minute	times/min	32-125	32-125	20-80	20-80	20-80
滑枕倾斜角度	Ram tilt angle	°	0-8	0-8	0-8	0-8	0-8
滑枕垂直调整距离	Ram vertical adjustment distance	mm	230	230	315	315	315
刀头支撑面到床身前壁间距离	Distance from cutter head to column surface	mm	485	485	600	600	600
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	320	320	490	490	690
工作台直径	Table diameter	mm	500	500	630	630	630
工作台纵向行程	Table longitudinal travel	mm	500	500	630	630	620
工作台横向行程	Table cross travel	mm	500	500	560	560	560
工作台最大回转角度	Table rotation angle	°	360	360	360	360	360
工作台纵横向机动进给量范围	Table feed range (longitudinal and cross)	mm	0.08-1.21	0.08-1.21	0.08-1.21	0.08-1.21	0.08-1.21
工作台回转进给范围	Table rotary feed range	mm	0.052-0.783	0.052-0.783	0.052-0.783	0.052-0.783	0.052-0.783
主电机功率	Main motor power	kw	3	3	4	4	4
快移电机功率	Rapid traverse motor power	kw	-	0.75	-	0.75	-
机床重量	Machine weight	kg	2200	2200	3000	3000	3700
外形尺寸(长×宽×高)	Overall dimension	mm	1916*1305*1995	1916*1305*1995	2261*1495*2245	2261*1495*2245	2290*1525*2485

主要技术参数	SPECIFICATIONS	Units	B5050	B5063	B50100	B51125
滑枕最大插削长度	Max. ram slotting length	mm	500	630	1000(内孔850)	1250(内孔1000)
滑枕运动次数	Ram moving frequency per minute	times/min	9-50	8-30	4-25/7-25	4-30/7-35
刀头支撑面到床身前壁间距离	Distance from cutter head to column surface	mm	990	1120	1120	1600
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	740	800	1140	1650
工作台直径	Table diameter	mm	1000	1120	1250	1400
工作台纵向行程	Table longitudinal travel	mm	660	1000	1200	1400
工作台横向行程	Table cross travel	mm	1000	700	1000	1120
工作台最大回转角度	Table rotation angle	°	360	360	360	360
工作台进给范围	Table feed range (longitudinal and cross)	mm	0.10-1.20	0.10-1.30	0.2-5	0.2-3
工作台回转进给范围	Table rotary feed range	mm	3-36	3-39	0.4-10	0.1-5
主电机功率	Main motor power	kw	7.5	11	37	37
机床重量	Machine weight	kg	10300	11000	22000	26000
外形尺寸(长×宽×高)	Overall dimension	mm	3480*2085*3307	3580*2390*3660	4400*2830*5730	4600*3200*6760

BK5018

CNC Slotting Machine 数控插床



BK5030 / BK5032

CNC Slotting Machine 数控插床



主要技术参数	SPECIFICATIONS	Units	BK5018
滑枕最大插削长度	Max. ram slotting length	mm	180
滑枕运动次数	Ram moving frequency per minute	times/min	20-120
滑枕垂直调整距离	Ram vertical adjustment distance	mm	80
刀头支撑面到床身前壁间距离	Distance from cutter head to column surface	mm	480
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	400
工作台尺寸	Table size	mm	600*320
工作台行程(X/Y)	Table travel (X/Y)	mm	320*320
X向电机扭矩	X axis motor torque	N.M	6
Y向电机扭矩	Y axis motor torque	N.M	6
X轴快速移动	X axis rapid traverse speed	m/min	5
Y轴快速移动	Y axis rapid traverse speed	m/min	5
主电机功率	Main motor power	kw	3.7
机床重量	Machine weight	kg	1800
外形尺寸(长×宽×高)	Overall dimension	mm	2200*2100*2300

主要技术参数	SPECIFICATIONS	Units	BK5030	BK5032
滑枕最大插削长度	Max. ram slotting length	mm	300	320
滑枕运动次数	Ram moving frequency per minute	times/min	30-180	20-80
滑枕垂直调整距离	Ram vertical adjustment distance	mm	300	315
刀头支撑面到床身前壁间距离	Distance from cutter head to column surface	mm	505	600
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	540	490
工作台尺寸	Table size	mm	550*405	600*320
工作台行程(X/Y)	Table travel (X/Y)	mm	280*330	620*560
X向电机扭矩	X axis motor torque	N.M	6	7.7
Y向电机扭矩	Y axis motor torque	N.M	6	7.7
X轴快速移动	X axis rapid traverse speed	m/min	5	5
Y轴快速移动	Y axis rapid traverse speed	m/min	5	5
主电机功率	Main motor power	kw	3.7	4
机床重量	Machine weight	kg	2700	3700
外形尺寸(长×宽×高)	Overall dimension	mm	2300*2200*2300	2800*2400*2500



B635A

Shaper Machine 刨床

主要技术参数	SPECIFICATIONS	Units	B635A
滑枕最大刨削长度	Max. ram shaping length	mm	350
滑枕运动次数	Ram moving frequency per minute	times/min	32-125
工作台尺寸	Table size	mm	350*300
工作台水平行程	Table horizontal travel	mm	400
工作台垂直行程	Table vertical travel	mm	270
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	330
刀架最大行程	Tool head travel	mm	110
刀架回转角度	Tool head tilt angle	°	±60
刀杆最大尺寸	Tool size	mm	20*30
工作台T型槽宽度	Table T-slot width		14
主电机功率	Main motor power	kw	1.5
机床重量	Machine weight	kg	1250
外形尺寸(长×宽×高)	Overall dimension	mm	1500*1100*1500



BC6085

Shaper Machine 刨床

BC6050 / BC6063 BC6066

Shaper Machine 刨床



BC60100

Shaper Machine 刨床



主要技术参数	SPECIFICATIONS	Units	B635A	BC6050	BC6063	BC6066
滑枕最大刨削长度	Max. ram shaping length	mm	350	500	630	660
滑枕运动次数	Ram moving frequency per minute	times/min	32-125	14-80	14-80	14-80
工作台尺寸	Table size	mm	350*300	440*360	630*400	660*400
工作台水平行程	Table horizontal travel	mm	400	525	630	630
工作台垂直行程	Table vertical travel	mm	270	270	360	360
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	330	370	385	385
刀架最大行程	Tool head travel	mm	110	120	120	120
刀架回转角度	Tool head tilt angle	°	±60	±60	±60	±60
刀杆最大尺寸	Tool size	mm	20*30	20*30	20*30	20*30
工作台T型槽宽度	Table T-slot width	mm	14	18	18	18
主电机功率	Main motor power	kw	1.5	3	3	3
机床重量	Machine weight	kg	1250	1760	1870	1920
外形尺寸(长×宽×高)	Overall dimension	mm	1500*1100*1500	2000*1300*1600	2000*1300*1650	2000*1300*1650

主要技术参数	SPECIFICATIONS	Units	BC6085	BC60100	BY60100
滑枕最大刨削长度	Max. ram shaping length	mm	850	1000	1000
滑枕运动次数	Ram moving frequency per minute	times/min	17-100	15-83	3-44
工作台尺寸	Table size	mm	800*450	1000*500	1000*500
工作台水平行程	Table horizontal travel	mm	710	800	800
工作台垂直行程	Table vertical travel	mm	360	380	380
滑枕底端到工作台面距离	Distance between ram lower end to table surface	mm	400	400	400
刀架最大行程	Tool head travel	mm	160	160	160
刀架回转角度	Tool head tilt angle	°	±60	±60	±60
刀杆最大尺寸	Tool size	mm	30*45	30*45	30*45
工作台T型槽宽度	Table T-slot width	mm	22	22	22
主电机功率	Main motor power	kw	5.5	7.5	7.5
机床重量	Machine weight	kg	3090	5150	5150
外形尺寸(长×宽×高)	Overall dimension	mm	2450*1450*1800	3700*1600*1800	3700*1600*1800